

Supplementary Material

September 7, 2014

1 Experiment on real networks

To illustrate the framework can reveal hidden robustness information of community structures in real networks, we apply it on three famous benchmarks comparing with their corresponding randomized network, i.e. Karate network [1], Collage football network [1] and Political books network [2]. These results are also in Table 1.

| α_C | Real network | Randomized network |
|--------------------------|--------------|--------------------|
| Karate network | 0.672 | 0.841 |
| Collage football network | 0.757 | 0.902 |
| Political books network | 0.698 | 0.881 |

Table 1: Comparison of α_C between real networks and corresponding randomized networks.

From this table, one can observe that the corresponding α_C value of real networks are all much smaller than randomized networks. Since random networks own few modularized structures, these results verify the effectiveness of our framework.

2 The relationship between networks establish mechanism and robustness

In order to verify our method, it is applied to three famous artificial networks— ER random graph, BA scale-free network, and $P\&S$ network [6] where the number of nodes are 10,000 nodes and the average degree is all 3. The comparison of the clustering coefficients ω and α_C is shown in the following table 1.

| Model | ER model | BA model | $P\&S$ model |
|------------|----------|----------|--------------|
| ω | 0.15 | 0.24 | 0.45 |
| α_C | 0.95 | 0.92 | 0.85 |

Table 2: The comparison of ω and α_C between three different types networks

Table 1 indicates that $P\&S$ model is the most robust one, for its generation mechanism includes both the similarity of nodes and the limited growth in the network, which are not available in BA and ER models. The similarity of nodes can be reflected by clustering coefficient and average degree indirectly, but does not affected by its degree distribution. BA model is more significant than ER model, and this can also be easily verified from their topology properties. These results are determined by the network building mechanism. ER network [4] is constructed by establishing a link between two isolate nodes with a probability p which lower than 1. BA network [5] is constructed based on two properties: growth property and preferential attachment property. According to the preferential attachment mechanism, new adding nodes are attached only preferential with older large degree nodes and this is not reasonable in many real networks. To overcome this defect, Papadopoulos et al. [6] proposed a new model which considers both popularity and similarity between new adding node and existing ones. The degree distribution of $P\&S$ network is scale-free which exactly same as BA network, however, the clustering coefficient is much larger. Thus, based on the robustness measure of γ_C , $P\&S$ is more robust than other two networks.

3 The relationships between our work and some famous concepts

In [7] introduced by Karrer et al, authors show that the robustness of community structure can be effectively quantified by measuring its robustness to small perturbations in network structure. They propose a suitable method for perturbing networks and a measure of the resulting change in community structure, i.e. the variation of information,

to quantify the robustness. This work mainly focus on comparing the difference of information between partition in real and corresponding random network. In contrast, our method doesnt need any partition and can be quantify the robustness information directly from the topology structure more easily.

In [8] written by Li et al, the authors propose a new framework to reveal hidden properties of community structures by quantitatively analyzing the dynamics of the Potts model. Specifically they model the Potts procedure of community structure detection by a Markov process, which show a given community is corresponding to a local uniform state. Critical topological information regarding multivariate spin configuration could also be inferred from the spectral significance of the Markov process, such as the optimal number of communities. Contrast to it, this work tries to unveil the dynamical detail of the robustness to perturbing of community structure. These two measures can all applied without using any particular partition algorithm. However, the objective and analysis measures between these two works are completely different.

References

- [1] Newman.M.E.J, Girvan,M. *Phys. Rev. E* **69**, 026113(2004).
- [2] Palla.G, Derényi.I, Farkas.I, Vicsek.T. *Nature* **435**, 814-818(2005).
- [3] Boyle.E.I et al. *Bioinformatics* **20**, 3710-3715(2004).
- [4] Erdős.P and Rényi.A. *Publ. Math. Inst. Hung. Acad. Sci.* **5**, 17-60(1960).
- [5] Barabási.A.L and Albert.R *Science* **286**, 509-512(1999).
- [6] Papadopoulos.F et al. *Nature* **489**, 537(2012).
- [7] Karrer.B, Levina.E and Newman.M.E.J. *Phys. Rev. E* **77**, 046119(2008).
- [8] Li.H.J, Wang.Y et al. *Europhys. Letts* **97**, 48005(2012).